## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Solight

Supplier's address: Solight, Solight Holding s.r.o. Lomnického 1705/5 140 00 Praha 4

## Model identifier: WZ323-1

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	G4				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	Ne		
Colour-tuneable light source:	Ne	Envelope:	-		
High luminance light source:	Ne				
Anti-glare shield:	Ne	Dimmable:	No		
Product parameters					

		Floudet para	lieters			
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the neares	00 h), rounded	2	Energy efficiency class	F		
Useful luminous indicating if it re in a sphere (36 cone (120º) or in (90º)	fers to the flux 0°, in a wide	130 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode po expressed in W	ower (P <sub>on</sub> ),	1,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, express rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	10	Spectral power	See image		
dimensions	Width	10	distribution in the	in last page		
without	Depth	10	-			
I	-	I	1	Strana 1		

separate control gear, lighting control parts and non- lighting control parts,		range 250 nm to 800 nm, at full-load	
if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity	0,440
		coordinates (x and y)	0,403
Parameters for LED and OLED light	nt sources:		
R9 colour rendering index value	10	Survival factor	0,90
the lumen maintenance factor	0,70		
(a),		1	

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

